



## Device Operation of polymer: fullerene bulk heterojunction solar cells

G. A. H. Wetzelaer<sup>1</sup>, M. Kuik<sup>1</sup>, N.I. Craciun<sup>2</sup> and P. W. M. Blom<sup>2</sup>

<sup>1</sup>Molecular Electronics, Zernike Institute for Advanced Materials, University of Groningen, Nijenborgh 4, 9747 AG Groningen, The Netherlands

<sup>2</sup>Max Planck Institute for Polymer Research, Ackermannweg 10, 55128 Mainz, Germany

In solar cells free charge carriers can recombine both via bimolecular (Langevin) and trap-assisted recombination (Shockley-Read-Hall). Trap-assisted recombination of electrons and holes is governed by capture coefficients that are thermally activated with an identical activation energy as measured for the hole mobility  $\mu_p$ . To elucidate which recombination mechanism is dominant in organic solar cells we investigated Charge-transfer (CT) state electroluminescence in several polymer: fullerene bulk heterojunction solar cells. The ideality factor of the electroluminescence reveals that the CT emission in polymer: fullerene solar cells originates from free-carrier bimolecular recombination at the donor-acceptor interface, rather than a charge trap-mediated process. These results are in agreement with measurements of the illumination-intensity dependence of the open-circuit voltage.

**Prof. Dr. P. W. M. Blom**  
Max Planck Institute  
for Polymer Research,  
Ackermannweg 10,  
55128 Mainz

**25. März 2014**  
**16:00 Uhr**  
**Campus Freudenberg**  
**FZH 3**